

INDUSTRIAL

PX940 Industrial Printer

PX940 Industrial Printer

Overview



The PX940 series takes industrial printing to a new level of accuracy and simplicity by providing customers with error-free precision printing, increasing production efficiency and reducing operational costs.

- Extremely precise printing of up to ± 0.2 mm (0.0079 in) virtually eliminates poor-quality, unreadable labels and barcodes.
- Integrated label verification technology checks and ensures that barcodes are accurate every time: instantly notifies you of pass/fail status and ANSI grade.
- Easy to use and maintain, with a color multilingual touchscreen interface and quick side-loading design.
- Smart printing capability allows users to configure and print without the need for a host computer.
- Operational Intelligence software provides predictive analytics and data on printer health to help managers oversee their entire printer fleet and proactively prevent issues, ensuring maximum uptime.

The PX940 family of high-performance industrial printers with integrated label verification technology provides error-free printing. Developed for companies that are subjected to fines levied for non-compliance to regulatory standards, and returned shipments due to unreadable barcodes, the PX940 series prints barcodes that are defect-free and 100% accurate every time. The fully integrated verifier allows for quick setting up even when printing and verifying different labels. With pass/fail and ANSI grades from 1 to 4, bad labels that do not meet an established threshold are voided and a new label is reprinted. The PX940 printer has print registration of up to ± 0.2 mm (0.0079 in). The trend toward miniaturization requires printing on smaller and smaller labels. The PX940 will print accurately on small labels, edge to edge with little error tolerance. The PX940 printers are suited for transportation and logistics, pharmaceuticals and healthcare, shipping and distribution centers, industrial manufacturing, automotive parts suppliers, and applications that are regulated and require high precision and error-free printing. The PX940 printer is available in two versions: one with the integrated verifier, and an option without the integrated verifier. Both versions are available with standard features such as Bluetooth® and smart printing capability, in which users can configure and fine-tune settings without the need for a host computer. With a Honeywell firmware platform that supports multiple print languages, the PX940 printer is an easy replacement for competitive printers. A rugged all-metal print mechanism, and easy printhead and tool-free platen roller replacement, help minimize downtime and maintenance needs. The PX940 printer can support a wide range of media –: including ink-in and ink-out ribbons with one-inch core size –: enabling maximum time between media resupply. Fast time-to-label and print speeds of up to 350 mm/s (14 ips) ensure that the PX940 printer can scale with the changing needs of dynamic operations.

Specifications

SPECIFICATIONS

FEATURES

Application

- Automotive
- DC/Warehouse
- Healthcare
- Manufacturing

Features

- Edge Intelligence Providing Customers with Predictive Analytics
- Integrated Label Verification Technology Providing Error-free Printing
- Precision Printing with Registration of +/-0.2 mm

Compatible Drivers

- CUPS Driver for Linux
- Certified Device Types for SAP
- InterDriver Windows

Compatible Software

- BarTender
- Nicelabel
- Operational Intelligence
- SOTI Connect
- Teklynx Labelview

DIMENSIONS

Overall Dimensions

- 50.6 x 39.87 x 26.1 cm (19.92 in x 15.70 in x 10.28 in)

Weight

- PX940 with Verifier: 23.5 kg (51.81 lbs)
- PX940: 23 kg (50.71 lbs)

SOFTWARE & FIRMWARE

2D Barcodes

- All major 2D barcodes

Linear Barcodes

- All major 1D barcodes

Downloadable Font Type

- Bitmap Font
- OpenType Font (TrueType based)
- TrueType Font

Printer Command Language

- C# Smart Printing
- DPL
- Fingerprint (FP)
- Intermec Printer Language (IPL)
- PDF
- WMSDirect Protocol (DP)
- XML-enabled for SAP All and Oracle WMS
- ZSim2 (ZPL-II)

Image File Format

- BMP
- GIF
- PCX
- PNG

Font Engine

- Monotype Font Engine
- WTLE for Global Language Support

PRINTING SPECIFICATIONS

Resolutions

- 203 dpi
- 300 dpi
- 600 dpi

Print Method

- Direct Thermal
- Thermal Transfer

Print Speeds

- 50-350mm/s (2-14 ips)

MEDIA

Printer Media Type

- Label
- RFID
- Ribbon
- Tag

Maximum Ribbon Length

- 450 m (1476 ft) foot

Maximum Media Roll Diameter

- 213 mm (8.38 in) inch

NETWORK

Wireless Communication

- Bluetooth LE
- NFC

Bluetooth Specifications

- Bluetooth LE (for Print Set MC only)

Network Specifications

- Ethernet 10/100 Mbps

MEMORY & DATA

RAM Memory

- 1 GB megabyte

Memory

- External Multi-GB USB memory device (FAT16/FAT32)

Flash Memory

- 256 MB megabyte

HARDWARE

Printer Connection Interface

- Applicator Interface
- Industrial interface
- Parallel Interface (IEEE 1284)
- RS-232
- USB 2.0 Host x2

ELECTRICAL

Operating voltage

- 100 - 240 V AC

Operating Frequency

- 50 - 60 Hz

ENVIRONMENTAL

Operating temperature

- +5°C to +40°C (+41°F to +104°F)

Operating Humidity

- 20 - 85 % non-condensing

Storage Humidity

- 20 - 85 % non-condensing

Storage Temperature

- -20°C to +70°C (-4°F to +152°F)

SERVICE TERMS

Warranty Duration

- One year factory warranty

ERP

Brand

- Honeywell

PRINTED BARCODE VERIFICATION

Verified Linear Barcodes

- Code 128
- Code 39
- EAN-128
- EAN-13
- EAN-8
- GS1 Databar Expanded
- GS1-128
- HIBC 128
- HIBC 39
- ISBT 128
- ITF-14
- Interleaved 2 of 5
- RSS14E
- SCC-14
- UPC-A
- UPC-E

Verification Standard

- ISO 15415/15416

Verified 2D Barcodes

- Data Matrix
- ISBT Data Matrix
- QR code

Verifier Scan Width

- 108mm (4.25 in)

Verifier Light Source Wavelength

- 660 nm

Verifier Scan Resolution

- 600 dpi

OTHERS

Platform

- Honeywell Printer Edge



Trade-In your old devices today and immediately get rewarded with a FREE extra year of service and FREE disposition of your old hardware!

[LEARN MORE NOW! →](#)

Honeywell

Industrial Automation
855 S Mint St
Charlotte, NC 28202
800-582-4263

PX940 Industrial Printer

© 2024 Honeywell International Inc.
All rights reserved.



This document was generated on 2024-07-23 12:16:07 PM (YYYY-MM-DD, HH:mm:ss). Subject to change without notice.